

SEMPLICE EFFETTO
SINGLE ACTING



PO5403/F

DOPPIO EFFETTO
DOUBLE ACTING



PO5405/F

Pompe manuali volumetriche alternative a semplice o doppio effetto costruite in acciaio al carbonio con componenti in alluminio e guarnizioni in Viton. Principali applicazioni: travasi, rabbocchi di olio ed antigelo da fusti.

Prestazioni rilevate in laboratorio alle seguenti condizioni: Olio idraulico viscosità ISO32 a 22°C
Portata rilevata a passaggio libero.

MODELLO MODEL	PO5403/F	PO5405/F
Portata Flow rate	12 lt/min	24 lt/min
Erogazione pompata Delivery per stroke	0.25 lt	0.48 lt.
Attacco uscita prodotto Fluid connection	M ¾" BSP	M ¾" BSP
Lunghezza pompante Pumping assy length	1000 mm	1000 mm
Ingombri (mm) Sizes (mm)	80x80x1350	80x80x1350
Per fusti da For drum capacity	208 lt	208 lt
Peso Weight	2,3 Kg.	2,8 Kg.

SEMPLICE EFFETTO
SINGLE ACTING



PO5410/F

DOPPIO EFFETTO
DOUBLE ACTING



PO5420/F

Volumetric single acting or double acting hand operated pumps made of carbon steel with aluminium components and Viton gaskets. Main applications transfer of fluids from drums.

Performances executed in the following conditions: Hydraulic oil viscosity ISO32 at 22°C -
Flow rate taken at free flow

MODELLO MODEL	PO5410/F	PO5420/F
Portata Flow rate	8 lt/min	16 lt/min
Erogazione pompata Delivery per stroke	0.13 lt	0.23 lt.
Attacco uscita prodotto Fluid connection	M ¾" BSP	M ¾" BSP
Lunghezza pompante Pumping assy length	1000 mm	1000 mm
Ingombri (mm) Sizes (mm)	80x80x1350	80x80x1350
Per fusti da For drum capacity	208 lt	208 lt
Peso Weight	2,2 Kg.	2,4 Kg.

Pompe manuali volumetriche alternative a semplice o doppio effetto costruite in acciaio al carbonio con componenti in alluminio. Principali applicazioni: travasi, rabbocchi di olio da fusti.

Volumetric single acting or double acting hand operated pumps made of carbon steel with aluminium components and Viton gaskets. Main application transfer of oil from drums.

CON PESCANTE TELESCOPICO
WITH TELESCOPIC PUMPING



PO5409/F



OTTIMALE PER LE OPERAZIONI DI TRAVASO CON TUBO PESCA TELESCOPICO E TUBO DI USCITA CURVATO IN ACCIAIO.

SUITABLE FOR TRANSFER OF OIL WITH TELESCOPIC PUMPING AND OUTPUT CURVED STEEL PIPE.



MODELLO MODEL	PO5409/F
Portata Flow rate	12 lt/min
Erogazione pompata Delivery per stroke	0.25 lt
Attacco uscita prodotto Fluid connection	ptg 20 mm
Lunghezza pompante Pumping assy length	1000 mm
Ingombri (mm) Sizes (mm)	100x100x944
Per fusti da For drum capacity	da 60 a 208 lt from 60 to 208 lt
Peso Weight	1,8 Kg.



POMPE A LEVA AD AZIONAMENTO MANUALE
CONSIGLIATE PER IDROCARBURI.
MANUAL LEVER PUMP SUGGESTED FOR
HYDROCARBON.